

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C11D 3/30, 17/06		A1	(11) International Publication Number: WO 98/38276
			(43) International Publication Date: 3 September 1998 (03.09.98)
(21) International Application Number: PCT/US98/02255		(81) Designated States: BR, CA, CN, JP, MX, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 18 February 1998 (18.02.98)			
(30) Priority Data: 60/039,409 28 February 1997 (28.02.97) US		Published With international search report.	
(71) Applicant: THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).			
(72) Inventors: HARTMAN, Frederick, Anthony; 10347 Deerfield Road, Cincinnati, OH 45242 (US). GODFROID, Robert, Allen; 5309 Whispering Woods Drive, West Chester, OH 45069 (US). LITTIG, Janet, Sue; 159 Hidden Hills Drive, Fairfield, OH 45014 (US). SIVIK, Mark, Robert; Apartment F, 40 Clubhouse Lane, Fairfield, OH 45014 (US).			
(74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).			
(54) Title: DETERGENT COMPOSITIONS HAVING COLOR CARE AGENTS			
(57) Abstract			
<p>Detergent composition having color care agents are provided. The detergent compositions comprise from about 0.1 % to about 50 % by weight of the composition of a color care agent having the formula: $(R_1)(R_2)N(CX_2)_nN(R_3)(R_4)$, wherein X is selected from the group consisting of hydrogen, linear or branched; substituted or unsubstituted alkyl having from 1-10 carbon atoms and substituted or unsubstituted aryl having at least 6 carbon atoms; n is an integer from 1 to 6; R₁, R₂, R₃, and R₄ are independently selected from the group consisting of alkyl, aryl, alkaryl, arylalk, hydroxyalkyl, polyhydroxyalkyl, polyalkylether having the formula: $((CH_2)_yO)_zR_7$ where R₇ is hydrogen or a linear, branched, substituted or unsubstituted alkyl chain having from 1 to 10 carbon atoms and where y is an integer from 2 to 10 and z is an integer from 1 to 30, alkoxy, polyalkoxy having the formula: $-(O(CH_2)_y)_zR_7$; the group $-C(O)R_8$ where R₈ is alkyl, alkaryl, arylalk, hydroxyalkyl, polyhydroxyalkyl and polyalkylether as defined in R₁, R₂, R₃, and R₄; $CX_2CX_2N(R_5)(R_6)$ with no more than one of R₁, R₂, R₃, and R₄ being $CX_2CX_2N(R_5)(R_6)$ and wherein R₅ and R₆ are alkyl, alkaryl, arylalk, hydroxyalkyl, polyhydroxyalkyl, polyalkylether, alkoxy and polyalkoxy as defined in R₁, R₂, R₃, and R₄; and either of R₁ + R₃ or R₄ or R₂ + R₃ or R₄ can combine to form a cyclic substituent. The compositions also include detergent adjunct ingredients including surfactants, builders, bleaching agents, enzymes, soil release polymers, dye transfer inhibitors, and mixtures thereof.</p>			

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan				

		KZ	Kazakhstan	RO	Romania
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation
DE	Germany	LI	Liechtenstein	SD	Sudan
DK	Denmark	LK	Sri Lanka	SE	Sweden
EE	Estonia	LR	Liberia	SG	Singapore

DETERGENT COMPOSITIONS HAVING COLOR CARE AGENTS

TECHNICAL FIELD

This case relates to detergent compositions having color care agents, and in particular, to granular laundry detergent compositions having color care agents.

BACKGROUND OF THE INVENTION

The formulation of detergent compositions which effectively removes a wide variety of soils and stains from fabrics under wide-ranging usage conditions remains a considerable challenge to the laundry detergent industry. The challenges associated with the formulation of truly effective cleaning compositions have been increased by legislation which limits the use of effective ingredients such as phosphate builders in many regions of the world.

In the meantime, colored items remain a large percentage of home or consumer laundered garments. These colored garments have an undesirable tendency to show appearance and color losses after multiple cycles through a laundry process. These appearance and color losses may be manifested after many multiples of cycles or only a few cycles through the laundry process. Thus, the usable lifetime of colored garments is reduced by the laundering process.

Accordingly, there is a need for detergent compositions which through the regular use of the composition can reduce or eliminate appearance and color losses due to the laundering process and thereby substantially increase the usable lifetime of colored garments. Also desired is a detergent composition which will not only reduce or eliminate color and appearance losses through regular use but which will also provide a noticeable appearance improvement to previously laundered garments which have undergone a degradation in appearance and/or color. Particularly desirable is a granular detergent composition with the aforementioned benefits.

SUMMARY OF THE INVENTION

The present invention discloses detergent compositions having a color care agent. In accordance with a first aspect of the present invention, a dryer-activated additive composition is provided. The composition comprises from about 0.1% to about 50% of

wherein X is selected from the group consisting of hydrogen, linear or branched, substituted or unsubstituted alkyl having from 1-10 carbon atoms and substituted or unsubstituted aryl having at least 6 carbon atoms; n is an integer from 0 to 6; R₁, R₂, R₃, and R₄ are independently selected from the group consisting of alkyl; aryl; alkaryl; arylalk; hydroxyalkyl; polyhydroxyalkyl; polyalkylether having the formula -((CH₂)_yO)_zR₇ where R₇ is hydrogen or a linear, branched, substituted or unsubstituted alkyl chain having from 1 to 10 carbon atoms and where y is an integer from 2 to 10 and z is an integer from 1 to 30; alkoxy; polyalkoxy having the formula: -(O(CH₂)_y)_zR₇; the group -C(O)R₈ where R₈ is alkyl; alkaryl; arylalk; hydroxyalkyl; polyhydroxyalkyl, and polyalkylether as defined in R₁, R₂, R₃, and R₄; CX₂CX₂N(R₅)(R₆) with no more than one of R₁, R₂, R₃, and R₄ being CX₂CX₂N(R₅)(R₆) and wherein R₅ and R₆ are alkyl; alkaryl; arylalk; hydroxyalkyl; polyhydroxyalkyl, polyalkylether, alkoxy and polyalkoxy as defined in R₁, R₂, R₃, and R₄; and either of R₁ + R₃ or R₄ or R₂ + R₃ or R₄ can combine to form a cyclic substituent; and from about 5% to about 99.9%, by weight, of detergent adjunct ingredients selected from the group consisting of surfactants, builders, bleaching agents, enzymes, soil release polymers, dye transfer inhibitors, and mixtures thereof.

Preferred compositions include those where R₁, R₂, R₃, and R₄ are independently selected from the group consisting of alkyl groups having from 1 to 5 carbon atoms and hydroxyalkyl groups having from 1 to 5 carbon atoms, preferably ethyl, methyl, hydroxyethyl, hydroxypropyl and isohydroxypropyl. The color care agent has more than about 1% nitrogen by weight of the compound, and preferably more than 7%.

The detergent composition preferably includes from about 5% to about 80%, by weight, of a detergent builder and from about 5% to about 80%, by weight, of deterative surfactant and is in granular form with a bulk density of at least about 550 g/L. The composition may also be in bar form or in liquid form in which case from about 5% to about 90% by weight of the composition of a liquid carrier is also included.

Accordingly, it is an object of the present invention to provide a detergent composition which through the regular use of the composition can reduce or eliminate appearance and color losses due to the laundering process and thereby substantially increase the usable lifetime of colored garments. It is also an object of the present invention to provide a detergent composition which can be used on colored garments without causing a degradation in appearance and or color. It is a feature of the present invention to provide

SUBSTITUTE SHEET (RULE 26)

a detergent composition having a color care agent or compound included in the composition or product. These and other objects, features and advantages of the present invention will be recognizable to one of ordinary skill in the art from the following description and the appended claims.


All percentages, ratios and proportions herein are on a weight basis unless otherwise indicated. All documents cited herein are hereby incorporated by reference. All viscosities are measured at a shear rate of 10 rpm on a Brookfield viscometer.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Color Care Agent

The detergent compositions of the present invention include a color care agent. The compositions may include from about 0.1% to about 50% by weight of the composition of the color care agent. More typically, the compositions comprise from about 0.1% to about 20%, preferably about 0.1% to about 10% and most preferably from about 0.5% to about 7% by weight of the composition of the color care agent.

The color care agent of the present invention is characterized by the formula:



In formula (I), X is selected from the group consisting of hydrogen, linear or branched, substituted or unsubstituted alkyl having from 1 to 10 carbon atoms and substituted or unsubstituted aryl having from 6 to 22 carbon atoms and n is an integer from 0 to 6. In addition, the group $-(CX_2)-$ may involve a cyclic group such as cyclic C_6H_{10} . Preferably X is hydrogen or a linear, unsubstituted alkyl chain having from 1 to 5 carbon atoms. However, branched chain alkyl groups such as isopropyl and isobutyl may also be employed. Most preferably, n is 2 or 3 and X is hydrogen, respectively resulting in the core structure $(R_1)(R_2)N(CH_2CH_2)_nN(R_3)(R_4)$.

As for the groups R_1 , R_2 , R_3 , and R_4 , each is individually or independently selected from the group consisting of hydrogen; alkyl; alkaryl; arylalk; hydroxyalkyl; polyhydroxyalkyl; polyalkylether having the formula $-((CH_2)_yO)_zR_7$ where R_7 is hydrogen or a linear, branched, substituted or unsubstituted alkyl chain having from 1 to 10 carbon atoms and where y is an integer from 2 to 10 and z is an integer from 1 to 30.

The available alkyl groups include linear or branched, substituted or unsubstituted alkyl groups typically having from about 1 to about 22 carbon atoms, preferably 1-10 carbon atoms. Most preferred alkyl groups include methyl, ethyl, propyl, and isopropyl. The available aryl groups include substituted or unsubstituted aryl groups typically having from about 6 to about 22 carbon atoms. Substitutions may include alkyl chains as earlier described thereby providing alkaryl or arylalk groups having from about 6 to about 22 carbon atoms. Preferred aryl, arylalk and alkaryl groups include phenyl, benzyl and mesityl. The available hydroxyalkyl and polyhydroxyalkyl groups include linear or branched, substituted or unsubstituted groups typically having from about 1 to about 22 carbon atoms. Preferred groups include hydroxymethyl, hydroxyethyl, 1-hydroxypropyl and 2-hydroxypropyl. The available polyalkoxy groups include those having the formula: $-(O(CH_2)_y)_zR_7$. The integer y typically ranges from 2 to about 10 with 1, 2, and 3 the most preferred. The group $-(CH_2)_y-$ may include both linear and branched chains. Preferred groups include methoxyl, ethoxyl and isopropoxyl. The integer z typically ranges from about 1 to 30 with lower levels of ethoxylation being preferred. R_7 is typically hydrogen or an alkyl groups having 1 to 5 carbon atoms. Polyalkylether having the formula $-((CH_2)_yO)_zR_7$ may also be employed in the present invention where the integer y typically ranges from 2 to about 10 with 1, 2, and 3 the most preferred, the group $-(CH_2)_y-$ may include both linear and branched chains with preferred groups including methoxyl, ethoxyl and isopropoxyl, the integer z typically ranges from about 1 to 30 with lower levels of ethoxylation being preferred and R_7 is typically hydrogen or an alkyl groups having 1 to 5 carbon atoms. The group $-C(O)R_8$ may also be employed where R_8 is alkyl; alkaryl; arylalk; hydroxyalkyl; polyhydroxyalkyl and polyalkylether as defined above.

R_1 , R_2 , R_3 , and R_4 may also be the group $CX_2CX_2N(R_5)(R_6)$. However, when the group is present, no more than one of R_1 , R_2 , R_3 , and R_4 at any one time may be the group $CX_2CX_2N(R_5)(R_6)$. Further, R_5 and R_6 are alkyl; alkaryl; arylalk; hydroxyalkyl; polyhydroxyalkyl, polyalkylether, alkoxy and polyalkoxy as defined in R_1 , R_2 , R_3 , and R_4 . Preferably, when any one of R_1 , R_2 , R_3 , and R_4 is present as the group $CX_2CX_2N(R_5)(R_6)$, then R_5 and R_6 are preferably, alkyl or hydroxyalkyl groups as defined above. Lastly, either of $R_1 + R_3$ or R_4 or $R_2 + R_3$ or R_4 can combine to form a cyclic substituent. Suitable examples include the moiety:

To provide suitable color care properties, the preferred color care agent materials according to the present invention consist of not less than 1% by weight of the compound of nitrogen, more preferably not less than 7% and most preferably not less than 9% by weight of the compound.

Most preferably, R₁, R₂, R₃, and R₄ are independently selected from the group consisting of linear alkyl groups having from 1 to 5 carbon atoms and linear hydroxyalkyl groups having from 1 to 5 carbon atoms. Especially preferred are the groups ethyl, methyl, hydroxyethyl and hydroxypropyl. While each of R₁, R₂, R₃, and R₄ may be individually selected, the preferred color care component according to the present invention involves the situation wherein each of R₁, R₂, R₃, and R₄ are hydroxyalkyl groups having from 1 to 5 carbon atoms. A preferred list of compounds includes N,N,N',N' tetraethylethylenediamine, 2-{{2-(dimethylamino)ethyl}-methylamino}ethanol, Bis-(2-hydroxyethyl)-N,N'-dimethylethylenediamine, Bis(octyl)-N,N'-dimethylethylenediamine, N,N,N',N'',N'' penta(2-hydroxypropyl)diethylenetriamine and N,N,N',N'-tetrakis(2-hydroxypropyl) ethylenediamine. Particularly preferred is N,N,N',N'-tetrakis(2-hydroxypropyl) ethylenediamine and N,N,N',N'',N'' penta(2-hydroxypropyl)diethylenetriamine. Such materials are commercially available from a number of sources including BASF of Washington, NJ under the tradename QUADROL and PENTROL.

Compositions

Compositions according to the present invention may include liquid, granular and bar compositions. Liquid compositions may include those in gel form. Effective detergent compositions may preferably include deterative surfactants and one or more members of detergent adjunct ingredients selected from the group consisting of bleaching agents, bleach stable thickeners, transition-metal chelants, builders, whitening agents (also known as brighteners) and buffering agents.

Detergent Adjunct Ingredients

As a preferred embodiment, the detergent ingredients employed herein can be selected from typical detergent composition components such as deterative surfactants and deterative builders. Optionally, the detergent ingredients can include one or more

detergent composition adjunct ingredients. Detergent adjuncts include the ingredients set forth in U.S. Pat. No. 3,936,537, Baskerville et al. Such adjuncts which

can be included in detergent compositions employed in the present invention, in levels for use (generally from 0% to about 80% of the detergent ingredients, preferably from about 0.5% to about 20%), include color speckles, suds boosters, suds suppressors, antitarnish and/or anticorrosion agents, soil-suspending agents, soil release agents, dyes, fillers, optical brighteners, germicides, alkalinity sources, hydrotropes, antioxidants, enzymes, enzyme stabilizing agents, solvents, solubilizing agents, chelating agents, clay soil removal/anti-redeposition agents, polymeric dispersing agents, processing aids, fabric softening components, static control agents, bleaching agents, bleaching activators, bleach stabilizers, etc.

(1) Bleaching Agents

(a) Source of hydrogen peroxide

Compositions according to the present invention may include a source of hydrogen peroxide. A source of hydrogen peroxide herein is any convenient compound or mixture which under consumer use conditions provides an effective amount of hydrogen peroxide. Levels may vary widely and are typically from about 0.1% to about 70%, more typically from about 0.2% to about 40% and even more typically from about 0.5% to about 25%, by weight of the bleaching compositions herein.

The source of hydrogen peroxide used herein can be any convenient source, including hydrogen peroxide itself. For example, perborate, e.g., sodium perborate (any hydrate but preferably the mono- or tetra-hydrate), sodium carbonate peroxyhydrate or equivalent percarbonate salts, sodium pyrophosphate peroxyhydrate, urea peroxyhydrate, or sodium peroxide can be used herein. Mixtures of any convenient hydrogen peroxide source can also be used.

A preferred percarbonate bleach comprises dry particles having an average particle size in the range from about 500 micrometers to about 1,000 micrometers, not more than about 10% by weight of said particles being smaller than about 200 micrometers and not more than about 10% by weight of said particles being larger than about 1,250 micrometers. Optionally, the percarbonate can be coated with silicate, borate or water-soluble surfactants. Percarbonate is available from various commercial sources such as FMC, Solvay and Tokai Denka.

(b) Bleach catalysts

As shown in Figure 1, the present invention provides a catalytic system comprising a transition metal cation of defined bleach catalytic activity, such as copper, iron, titanium,

ruthenium tungsten, molybdenum, or manganese cations, an auxiliary metal cation having little or no bleach catalytic activity, such as zinc or aluminum cations, and a sequester having defined stability constants for the catalytic and auxiliary metal cations, particularly ethylenediaminetetraacetic acid, ethylenediaminetetra(methylenephosphonic acid) S,S-ethylenediamine disuccinic acid and water-soluble salts thereof. Such catalysts are disclosed in U.S. Pat. 4,430,243.

Other types of bleach catalysts include the manganese-based complexes disclosed in U.S. Pat. 5,246,621 and U.S. Pat. 5,244,594. Preferred examples of these catalysts include $\text{Mn}^{\text{IV}}_2(\text{u-O})_3(1,4,7\text{-trimethyl-}1,4,7\text{-triazacyclononane})_2(\text{PF}_6)_2$ ("MnTACN"), $\text{Mn}^{\text{III}}_2(\text{u-O})_1(\text{u-OAc})_2(1,4,7\text{-trimethyl-}1,4,7\text{-triazacyclononane})_2(\text{ClO}_4)_2$, $\text{Mn}^{\text{IV}}_4(\text{u-O})_6(1,4,7\text{-triazacyclononane})_4(\text{ClO}_4)_2$, $\text{Mn}^{\text{III}}\text{Mn}^{\text{IV}}_4(\text{u-O})_1(\text{u-OAc})_2(1,4,7\text{-trimethyl-}1,4,7\text{-triazacyclononane})_2(\text{ClO}_4)_3$, $\text{Mn}^{\text{III}}\text{Mn}^{\text{IV}}_4(\text{u-O})_2(\text{u-OAc})_1(1,4,7\text{-trimethyl-}1,4,7\text{-triazacyclononane})_2(\text{ClO}_4)_3$ and mixtures thereof. See also European patent application publication no. 549,272. Other ligands suitable for use herein include 1,5,9-trimethyl-1,5,9-triazacyclododecane, 2-methyl-1,4,7-triazacyclononane, and mixtures thereof. For examples of other suitable bleach catalysts herein see U.S. Pat. 4,246,612, U.S. Pat. 5,227,084 and WO 95/34628, December 21, 1995, the latter relating to particular types of iron catalyst. See also U.S. Pat. 5,194,416 which teaches mononuclear manganese (IV) complexes such as $\text{Mn}(1,4,7\text{-trimethyl-}1,4,7\text{-triazacyclononane}(\text{OCH}_3)_3)_3(\text{PF}_6)$.

Still another type of bleach catalyst, as disclosed in U.S. Pat. 5,114,606, is a water-soluble complex of manganese (II), (III), and/or (IV) with a ligand which is a non-carboxylate polyhydroxy compound having at least three consecutive C-OH groups. Preferred ligands include sorbitol, iditol, dulcitol, mannitol, xylitol, arabitol, adonitol, meso-erythritol, meso-inositol, lactose, and mixtures thereof.

U.S. Pat. 5,114,611 teaches another useful bleach catalyst comprising a complex of transition metals, including Mn, Co, Fe, or Cu, with a non-(macro)-cyclic ligand. Preferred ligands include pyridine, pyridazine, pyrimidine, pyrazine, imidazole, pyrazole, and triazole rings. Optionally, said rings may be substituted with substituents such as alkyl, aryl, alkoxy, halide, and nitro. Particularly preferred is the ligand 2,2'-bispyridylamine. Preferred bleach catalysts include Co-, Cu-, Mn-, or Fe-bispyridylmethane and bispyridylamine complexes. Highly preferred catalysts include $\text{Co}(2,2'\text{-bispyridylamine})\text{Cl}_2$. $\text{Di}(\text{isothiocyanato})\text{bispyridylamine-cobalt}^{\text{II}}$ (11)

Other bleach catalyst examples include Mn gluconate, $\text{Mn}(\text{CF}_3\text{SO}_3)_2$, $\text{Co}(\text{NH}_3)_5\text{Cl}$, and the binuclear Mn complexed with tetra-N-dentate and bi-N-dentate ligands, including $\text{N}_4\text{Mn}^{\text{III}}(\text{u-O})_2\text{Mn}^{\text{IV}}\text{N}_4)^+$ and $[\text{Bipy}_2\text{Mn}^{\text{III}}(\text{u-O})_2\text{Mn}^{\text{IV}}\text{bipy}_2](\text{ClO}_4)_3$.

Other bleach catalysts are described, for example, in European patent application, publication no. 408,131 (cobalt complex catalysts), European patent applications, publication nos. 384,503, and 306,089 (metallo-porphyrin catalysts), U.S. 4,728,455 (manganese/multidentate ligand catalyst), U.S. 4,711,748 and European patent application, publication no. 224,952, (absorbed manganese on aluminosilicate catalyst), U.S. 4,601,845 (aluminosilicate support with manganese and zinc or magnesium salt), U.S. 4,626,373 (manganese/ligand catalyst), U.S. 4,119,557 (ferric complex catalyst), German Pat. specification 2,054,019 (cobalt chelant catalyst) Canadian 866,191 (transition metal-containing salts), U.S. 4,430,243 (chelants with manganese cations and non-catalytic metal cations), and U.S. 4,728,455 (manganese gluconate catalysts).

These catalysts may be coprocessed with adjunct materials so as to reduce the color impact if desired for the aesthetics of the product, or to be included in enzyme-containing particles as exemplified hereinafter, or the compositions may be manufactured to contain catalyst "speckles".

Organic bleach catalysts may also be employed in the present invention. Organic bleach catalysts are known and include imine compounds and their precursors as disclosed in U.S. Patent Nos. 5,360,568, 5,360,569, and 5,370,826, the disclosures of which are all herein incorporated by reference and the sulfonyl imine compounds, their precursors and bleaching agents as disclosed in U.S. Patent Nos. 5,041,232, 5,045,223, 5,047,163, 5,310,925, 5,413,733, 5,429,768 and 5,463,115 the disclosures of which are all herein incorporated by reference.

Particularly preferred organic bleach catalysts include quaternary imine zwitterions as disclosed in U.S. Patent No. 5,576,282 to Miracle et al and include 3-(3,4-dihydroisoquinolinium)propane sulfonate 4-(3,4-dihydroisoquinolinium)butane sulfonate.

As a practical matter, and not by way of limitation, the compositions herein can be adjusted to provide on the order of at least one part per hundred million of the active bleach catalyst species in the aqueous washing medium and will preferably be at least


in order to obtain such levels in the wash liquor of an automatic dishwashing process, typical automatic dishwashing compositions herein will comprise

from about 0.0005% to about 0.2%, more preferably from about 0.004% to about 0.08%, of bleach catalyst by weight of the cleaning compositions.

(c) Bleach Activators

Compositions of the present invention may also include a bleach activator. Numerous bleach activators are known and are optionally included in the instant bleaching compositions. Various nonlimiting examples of such activators are disclosed in U.S. Patent 4,915,854, issued April 10, 1990 to Mao et al, and U.S. Patent 4,412,934. The nonanoyloxybenzene sulfonate (NOBS) and tetraacetyl ethylenediamine (TAED) activators are typical, and mixtures thereof can also be used. See also U.S. 4,634,551 for other typical conventional bleach activators. Known amido-derived bleach activators are those of the formulae: $R^1N(R^5)C(O)R^2C(O)L$ or $R^1C(O)N(R^5)R^2C(O)L$ wherein R^1 is an alkyl group containing from about 6 to about 12 carbon atoms, R^2 is an alkylene containing from 1 to about 6 carbon atoms, R^5 is H or alkyl, aryl, or alkaryl containing from about 1 to about 10 carbon atoms, and L is any suitable leaving group. A further class of bleach activator useful in the present invention includes unsymmetrical acyclic imide activators having the formula:

(I)




wherein R_1 is a C_7 - C_{13} linear or branched chain saturated or unsaturated alkyl group, R_2 is a C_1 - C_8 , linear or branched chain saturated or unsaturated alkyl group and R_3 is a C_1 - C_4 linear or branched chain saturated or unsaturated alkyl group. Suitable examples include N-octanoyl-N-methyl acetamide, N-nonanoyl-N-methyl acetamide, N-decanoyl-N-methyl acetamide and N-dodecanoyl-N-methyl acetamide.

Further illustration of bleach activators of the above formulae include (6-octanamido-caproyl)oxybenzenesulfonate, (6-nonanamidocaproyl)oxybenzenesulfonate, (6-decanamido-caproyl)oxybenzenesulfonate, and mixtures thereof as described in U.S. Patent 4,634,551. Another class of conventional bleach activators comprises the benzoxazin-type activators disclosed by Hodge et al in U.S. Patent 4,966,723, issued October 30, 1990. Examples of optional bleach activators include:


caprolactam, nitrobenzoyl caprolactam, undecenoyl valerolactam, nonanoyl valerolactam, 3,5,5-trimethylhexanoyl valerolactam and mixtures thereof.

conjunction with the present invention. One class of suitable organic peroxycarboxylic acids have the general formula:




wherein R is an alkylene or substituted alkylene group containing from 1 to about 22 carbon atoms or a phenylene or substituted phenylene group, and Y is hydrogen, halogen, alkyl, aryl, -C(O)OH or -C(O)OOH.

Organic peroxyacids suitable for use in the present invention can contain either one or two peroxy groups and can be either aliphatic or aromatic. When the organic peroxycarboxylic acid is aliphatic, the unsubstituted acid has the general formula:



where Y can be, for example, H, CH₃, CH₂Cl, C(O)OH, or C(O)OOH; and n is an integer from 1 to 20. When the organic peroxycarboxylic acid is aromatic, the unsubstituted acid has the general formula:



wherein Y can be, for example, hydrogen, alkyl, alkylhalogen, halogen, C(O)OH or C(O)OOH.

Typical monoperoxy acids useful herein include alkyl and aryl peroxyacids such as:

- (i) peroxybenzoic acid and ring-substituted peroxybenzoic acid, e.g. peroxy-a-naphthoic acid, monoperoxyphthalic acid (magnesium salt hexahydrate), and *o*-carboxybenzamidoperoxyhexanoic acid (sodium salt);
- (ii) aliphatic, substituted aliphatic and arylalkyl monoperoxy acids, e.g. peroxyauric acid, peroxystearic acid, N-nonanoylaminoperoxycaproic acid (NAPCA), N,N-(3-octylsuccinoyl)aminoperoxycaproic acid (SAPA) and N,N-phthaloylaminoperoxycaproic acid (PAP);
- (iii) amidoperoxyacids, e.g. monononylamide of either peroxysuccinic acid (NAPSA) or of peroxyadipic acid (NAPAA).

Typical diperoxyacids useful herein include alkyl diperoxyacids and

- (vi) diperoxybrassylic acid; diperoxysebacic acid and diperoxyisophthalic acid;
- (vii) 2-decyldiperoxybutane-1,4-dioic acid;
- (viii) 4,4'-sulfonylbisperoxybenzoic acid.

(2) Deterative Surfactant

The compositions of the present invention may include a deterative surfactant. The deterative surfactant may comprise from about 1%, to about 99.8%, by weight of the composition depending upon the particular surfactants used and the effects desired. More typical levels comprise from about 5% to about 80% by weight of the composition.

The deterative surfactant can be nonionic, anionic, ampholytic, zwitterionic, or cationic. Mixtures of these surfactants can also be used. Preferred detergent compositions comprise anionic deterative surfactants or mixtures of anionic surfactants with other surfactants, especially nonionic surfactants.

Nonlimiting examples of surfactants useful herein include the conventional C₁₁-C₁₈ alkyl benzene sulfonates and primary, secondary and random alkyl sulfates, the C₈-C₁₈ alkyl alkoxy sulfates, the C₈-C₁₈ alkyl polyglycosides and their corresponding sulfated polyglycosides, C₈-C₁₈ alpha-sulfonated fatty acid esters, C₈-C₁₈ alkyl and alkyl phenol alkoxylates (especially ethoxylates and mixed ethoxy/propoxy), C₈-C₁₈ betaines and sulfobetaines ("sultaines"), C₈-C₁₈ amine oxides, such as branched or unbranched aliphatic N,N-dimethyl-N-oxides and the like. Other conventional useful surfactants are listed in standard texts such as *Surfactants in Consumer Products; Theory, Technology and Application*, J. Falbe, ed. Springer-Verlag 1987 and *Handbook of Surfactants*, M.R. Porter, Blackie & Son, 1991.

One class of nonionic surfactant particularly useful in detergent compositions of the present invention is condensates of ethylene oxide with a hydrophobic moiety to provide a surfactant having an average hydrophilic-lipophilic balance (HLB) in the range of from 5 to 17, preferably from 6 to 16, more preferably from 7 to 15. The hydrophobic (lipophilic) moiety may be aliphatic or aromatic in nature. The length of the polyoxyethylene group which is condensed with any particular hydrophobic group can be readily adjusted to yield a water-soluble compound having the desired degree of balance between hydrophilic and hydrophobic elements.

For example, the C₁₂-C₁₅ primary alcohols containing 3-5 moles of ethylene oxide per mole of alcohol, the C₁₂-C₁₅ primary alcohols containing 3-5 moles of ethylene oxide

per mole of alcohol, the C₉-C₁₁ primary alcohols containing 8-12 moles of ethylene oxide per mole of alcohol, and mixtures thereof. Suitable ethoxylated fatty alcohol nonionic surfactants for use in the present invention are commercially available under the tradenames DOBANOL and NEODOL available from the Shell Oil Company of Houston, Texas.

Another suitable class of nonionic surfactants comprises the polyhydroxy fatty acid amides of the formula:



wherein: R¹ is H, C₁-C₈ hydrocarbyl, 2-hydroxyethyl, 2-hydroxypropyl, or a mixture thereof, preferably C₁-C₂ alkyl, more preferably C₁ or C₂ alkyl, most preferably C₁ alkyl (i.e., methyl); and R² is a C₅-C₃₂ hydrocarbyl moiety, preferably straight chain C₇-C₁₉ alkyl or alkenyl, more preferably straight chain C₉-C₁₇ alkyl or alkenyl, most preferably straight chain C₁₁-C₁₉ alkyl or alkenyl, or mixture thereof; and Z is a polyhydroxyhydrocarbyl moiety having a linear hydrocarbyl chain with at least 2 (in the case of glyceraldehyde) or at least 3 hydroxyls (in the case of other reducing sugars) directly connected to the chain, or an alkoxyated derivative (preferably ethoxylated or propoxylated) thereof. Z preferably will be derived from a reducing sugar in a reductive amination reaction; more preferably Z is a glycityl moiety. Suitable reducing sugars include glucose, fructose, maltose, lactose, galactose, mannose, and xylose, as well as glyceraldehyde. As raw materials, high dextrose corn syrup, high fructose corn syrup, and high maltose corn syrup can be utilized as well as the individual sugars listed above. These corn syrups may yield a mix of sugar components for Z. It should be understood that it is by no means intended to exclude other suitable raw materials. Z preferably will be selected from the group consisting of -CH₂-(CHOH)_n-CH₂OH, -CH(CH₂OH)-(CHOH)_{n-1}-CH₂OH, -CH₂-(CHOH)₂(CHOR')(CHOH)-CH₂OH, where n is an integer from 1 to 5, inclusive, and R' is H or a cyclic mono- or poly- saccharide, and alkoxyated derivatives thereof. Most preferred are glycityls wherein n is 4, particularly -CH₂-(CHOH)₄-CH₂OH.

In Formula (I), R¹ can be, for example, N-methyl, N-ethyl, N-propyl, N-isopropyl, N-butyl, N-isobutyl, N-2-hydroxy ethyl, or N-2-hydroxy propyl. For highest sudsing, R¹ is preferably methyl or hydroxyalkyl. If lower sudsing is desired, R¹ is preferably C₂-C₈ alkyl, especially n-propyl, iso-propyl, n-butyl, iso-butyl, pentyl, hexyl and 2-ethyl hexyl.

(3) Builders

Detergent builders can optionally be included in the compositions herein to assist in controlling mineral hardness. Inorganic as well as organic builders can be used. Builders are typically used in fabric laundering compositions to assist in the removal of particulate soils.

The level of builder can vary widely depending upon the end use of the composition and its desired physical form. When present, the compositions will typically comprise at least about 1% builder. High performance compositions typically comprise from about 10% to about 80%, more typically from about 15% to about 50% by weight, of the detergent builder. Lower or higher levels of builder, however, are not excluded.

Inorganic or P-containing detergent builders include, but are not limited to, the alkali metal, ammonium and alkanolammonium salts of polyphosphates (exemplified by the tripolyphosphates, pyrophosphates, and glassy polymeric meta-phosphates), phosphonates, phytic acid, silicates, carbonates (including bicarbonates and sesquicarbonates), sulphates, and aluminosilicates. However, non-phosphate builders are required in some locales. Importantly, the compositions herein function surprisingly well even in the presence of the so-called "weak" builders (as compared with phosphates) such as citrate, or in the so-called "underbuilt" situation that may occur with zeolite or layered silicate builders. See U.S. Pat. 4,605,509 for examples of preferred aluminosilicates.

Examples of silicate builders are the alkali metal silicates, particularly those having a $\text{SiO}_2:\text{Na}_2\text{O}$ ratio in the range 1.6:1 to 3.2:1 and layered silicates, such as the layered sodium silicates described in U.S. Patent 4,664,839, issued May 12, 1987 to H. P. Rieck. NaSKS-6® is a crystalline layered silicate marketed by Hoechst (commonly abbreviated herein as "SKS-6"). Unlike zeolite builders, the Na SKS-6 silicate builder does not contain aluminum. NaSKS-6 is the $\delta\text{-Na}_2\text{SiO}_5$ morphology form of layered silicate and can be prepared by methods such as those described in German DE-A-3,417,649 and DE-A-3,742,043. SKS-6 is a highly preferred layered silicate for use herein, but other such layered silicates, such as those having the general formula $\text{NaMSi}_x\text{O}_{2x+1}\cdot y\text{H}_2\text{O}$ wherein M is sodium or hydrogen, x is a number from 1.9 to 4, preferably 2, and y is a number from 0 to 20, preferably 0 can be used herein. Various other layered silicates are known in the art.

As noted above, the compositions herein can be used as a detergent, as a bleaching agent for oxygen bleaches, and as a component of suds control systems.

Silicates useful in automatic dishwashing (ADD) applications include granular hydrous 2-ratio silicates such as BRITESIL® H20 from PQ Corp., and the commonly sourced BRITESIL® H24 though liquid grades of various silicates can be used when the ADD composition has liquid form. Within safe limits, sodium metasilicate or sodium hydroxide alone or in combination with other silicates may be used in an ADD context to boost wash pH to a desired level.

Examples of carbonate builders are the alkaline earth and alkali metal carbonates as disclosed in German Patent Application No. 2,321,001 published on November 15, 1973. Various grades and types of sodium carbonate and sodium sesquicarbonate may be used, certain of which are particularly useful as carriers for other ingredients, especially deterative surfactants.

Aluminosilicate builders are useful in the present invention. Aluminosilicate builders are of great importance in most currently marketed heavy duty granular detergent compositions, and can also be a significant builder ingredient in liquid detergent formulations. Aluminosilicate builders include those having the empirical formula: $[M_z(zAlO_2)_y] \cdot xH_2O$ wherein z and y are integers of at least 6, the molar ratio of z to y is in the range from 1.0 to about 0.5, and x is an integer from about 15 to about 264.

Useful aluminosilicate ion exchange materials are commercially available. These aluminosilicates can be crystalline or amorphous in structure and can be naturally-occurring aluminosilicates or synthetically derived. A method for producing aluminosilicate ion exchange materials is disclosed in U.S. Patent 3,985,669, Krummel, et al, issued October 12, 1976. Preferred synthetic crystalline aluminosilicate ion exchange materials useful herein are available under the designations Zeolite A, Zeolite P (B), Zeolite MAP and Zeolite X. In an especially preferred embodiment, the crystalline aluminosilicate ion exchange material has the formula: $Na_{12}[(AlO_2)_{12}(SiO_2)_{12}] \cdot xH_2O$ wherein x is from about 20 to about 30, especially about 27. This material is known as Zeolite A. Dehydrated zeolites ($x = 0 - 10$) may also be used herein. Preferably, the aluminosilicate has a particle size of about 0.1-10 microns in diameter. As with other builders such as carbonates, it may be desirable to use zeolites in any physical or morphological form adapted to promote surfactant carrier function, and appropriate particle sizes may be freely selected by the formulator.

Another class of carboxylate builders are compounds having a plurality of carboxylate groups, preferably at least 3 carboxylates. Polycarboxylate builder can generally be added to the

composition in acid form, but can also be added in the form of a neutralized salt or "overbased". When utilized in salt form, alkali metals, such as sodium, potassium, and lithium, or alkanolammonium salts are preferred.

Included among the polycarboxylate builders are a variety of categories of useful materials. One important category of polycarboxylate builders encompasses the ether polycarboxylates, including oxydisuccinate, as disclosed in Berg, U.S. Patent 3,128,287, issued April 7, 1964, and Lamberti et al, U.S. Patent 3,635,830, issued January 18, 1972. See also "TMS/TDS" builders of U.S. Patent 4,663,071, issued to Bush et al, on May 5, 1987. Suitable ether polycarboxylates also include cyclic compounds, particularly alicyclic compounds, such as those described in U.S. Patents 3,923,679; 3,835,163; 4,158,635; 4,120,874 and 4,102,903.

Other useful detergency builders include the ether hydroxypolycarboxylates, copolymers of maleic anhydride with ethylene or vinyl methyl ether, 1, 3, 5-trihydroxy benzene-2, 4, 6-trisulphonic acid, and carboxymethyloxysuccinic acid, the various alkali metal, ammonium and substituted ammonium salts of polyacetic acids such as ethylenediaminetetraacetic acid and nitrilotriacetic acid, as well as polycarboxylates such as mellitic acid, succinic acid, oxydisuccinic acid, polymaleic acid, benzene 1,3,5-tricarboxylic acid, carboxymethyloxysuccinic acid, and soluble salts thereof.

Citrate builders, e.g., citric acid and soluble salts thereof (particularly sodium salt), are polycarboxylate builders of particular importance for heavy duty laundry detergent formulations due to their availability from renewable resources and their biodegradability. Citrates can also be used in combination with zeolite and/or layered silicate builders. Oxydisuccinates are also especially useful in such compositions and combinations.

Also suitable in the detergent compositions of the present invention are the 3,3-dicarboxy-4-oxa-1,6-hexanedioates and the related compounds disclosed in U.S. Patent 4,566,984, Bush, issued January 28, 1986. Useful succinic acid builders include the C₅-C₂₀ alkyl and alkenyl succinic acids and salts thereof. A particularly preferred compound of this type is dodecenylsuccinic acid. Specific examples of succinate builders include: laurylsuccinate, myristylsuccinate, palmitylsuccinate, 2-dodecenylsuccinate (preferred), 2-pentadecenylsuccinate, and the like. Laurylsuccinates are the preferred builders of this group, and are described in European Patent Application 86200690.5/0 200 263, published 1997.

See also U.S. Patent 3,723,322.

SUBSTITUTE SHEET (RULE 26)

Fatty acids, e.g., C₁₂-C₁₈ monocarboxylic acids, can also be incorporated into the compositions alone, or in combination with the aforesaid builders, especially citrate and/or the succinate builders, to provide additional builder activity. Such use of fatty acids will generally result in a diminution of sudsing, which should be taken into account by the formulator.

In situations where phosphorus-based builders can be used, and especially in the formulation of bars used for hand-laundrying operations, the various alkali metal phosphates such as the well-known sodium tripolyphosphates, sodium pyrophosphate and sodium orthophosphate can be used. Phosphonate builders such as ethane-1-hydroxy-1,1-diphosphonate and other known phosphonates (see, for example, U.S. Patents 3,159,581; 3,213,030; 3,422,021; 3,400,148 and 3,422,137) can also be used. However, in general, phosphorous-based builders are not desired.

(4) Polymeric Soil Release Agent

Any polymeric soil release agent known to those skilled in the art can optionally be employed in the compositions and processes of this invention. Polymeric soil release agents are characterized by having both hydrophilic segments, to hydrophilize the surface of hydrophobic fibers, such as polyester and nylon, and hydrophobic segments, to deposit upon hydrophobic fibers and remain adhered thereto through completion of washing and rinsing cycles and, thus, serve as an anchor for the hydrophilic segments. This can enable stains occurring subsequent to treatment with the soil release agent to be more easily cleaned in later washing procedures.

The polymeric soil release agents useful herein especially include those soil release agents having: (a) one or more nonionic hydrophile components consisting essentially of (i) polyoxyethylene segments with a degree of polymerization of at least 2, or (ii) oxypropylene or polyoxypropylene segments with a degree of polymerization of from 2 to 10, wherein said hydrophile segment does not encompass any oxypropylene unit unless it is bonded to adjacent moieties at each end by ether linkages, or (iii) a mixture of oxyalkylene units comprising oxyethylene and from 1 to about 30 oxypropylene units wherein said mixture contains a sufficient amount of oxyethylene units such that the hydrophile component has hydrophilicity great enough to increase the hydrophilicity of conventional polyester synthetic fiber surfaces upon deposit of the soil release agent.

or (b) one or more hydrophobe components comprising (i) C₃ oxyalkylene terephthalate

segments, wherein, if said hydrophobe components also comprise oxyethylene terephthalate, the ratio of oxyethylene terephthalate:C₃ oxyalkylene terephthalate units is about 2:1 or lower, (ii) C₄-C₆ alkylene or oxy C₄-C₆ alkylene segments, or mixtures therein, (iii) poly (vinyl ester) segments, preferably polyvinyl acetate, having a degree of polymerization of at least 2, or (iv) C₁-C₄ alkyl ether or C₄ hydroxyalkyl ether substituents, or mixtures therein, wherein said substituents are present in the form of C₁-C₄ alkyl ether or C₄ hydroxyalkyl ether cellulose derivatives, or mixtures therein, and such cellulose derivatives are amphiphilic, whereby they have a sufficient level of C₁-C₄ alkyl ether and/or C₄ hydroxyalkyl ether units to deposit upon conventional polyester synthetic fiber surfaces and retain a sufficient level of hydroxyls, once adhered to such conventional synthetic fiber surface, to increase fiber surface hydrophilicity, or a combination of (a) and (b).

Typically, the polyoxyethylene segments of (a)(i) will have a degree of polymerization of from about 200, although higher levels can be used, preferably from 3 to about 150, more preferably from 6 to about 100. Suitable oxy C₄-C₆ alkylene hydrophobe segments include, but are not limited to, end-caps of polymeric soil release agents such as $\text{MO}_3\text{S}(\text{CH}_2)_n\text{OCH}_2\text{CH}_2\text{O}-$, where M is sodium and n is an integer from 4-6, as disclosed in U.S. Patent 4,721,580, issued January 26, 1988 to Gosselink.

Polymeric soil release agents useful in the present invention also include cellulosic derivatives such as hydroxyether cellulosic polymers, copolymeric blocks of ethylene terephthalate or propylene terephthalate with polyethylene oxide or polypropylene oxide terephthalate, and the like. Such agents are commercially available and include hydroxyethers of cellulose such as METHOCEL (Dow). Cellulosic soil release agents for use herein also include those selected from the group consisting of C₁-C₄ alkyl and C₄ hydroxyalkyl cellulose; see U.S. Patent 4,000,093, issued December 28, 1976 to Nicol, et al.

Soil release agents characterized by poly(vinyl ester) hydrophobe segments include graft copolymers of poly(vinyl ester), e.g., C₁-C₆ vinyl esters, preferably poly(vinyl acetate) grafted onto polyalkylene oxide backbones, such as polyethylene oxide backbones. See European Patent Application 0 219 048, published April 22, 1987 by Kud, et al. Commercially available soil release agents of this kind include the SOKALAN type of material, e.g., SOKALAN HP-22, available from BASF (West

weight of this polymeric soil release agent is in the range of from about 25,000 to about

55,000. See U.S. Patent 3,959,230 to Hays, issued May 25, 1976 and U.S. Patent 3,893,929 to Basadur issued July 8, 1975.

Another preferred polymeric soil release agent is a polyester with repeat units of ethylene terephthalate units containing 10-15% by weight of ethylene terephthalate units together with 90-80% by weight of polyoxyethylene terephthalate units, derived from a polyoxyethylene glycol of average molecular weight 300-5,000. Examples of this polymer include the commercially available material ZELCON 5126 (from Dupont) and MILEASE T (from ICI). See also U.S. Patent 4,702,857, issued October 27, 1987 to Gosselink.

Another preferred polymeric soil release agent is a sulfonated product of a substantially linear ester oligomer comprised of an oligomeric ester backbone of terephthaloyl and oxyalkyleneoxy repeat units and terminal moieties covalently attached to the backbone. These soil release agents are described fully in U.S. Patent 4,968,451, issued November 6, 1990 to J.J. Scheibel and E.P. Gosselink. Other suitable polymeric soil release agents include the terephthalate polyesters of U.S. Patent 4,711,730, issued December 8, 1987 to Gosselink et al, the anionic end-capped oligomeric esters of U.S. Patent 4,721,580, issued January 26, 1988 to Gosselink, and the block polyester oligomeric compounds of U.S. Patent 4,702,857, issued October 27, 1987 to Gosselink.

Preferred polymeric soil release agents also include the soil release agents of U.S. Patent 4,877,896, issued October 31, 1989 to Maldonado et al, which discloses anionic, especially sulfoaroyl, end-capped terephthalate esters.

Still another preferred soil release agent is an oligomer with repeat units of terephthaloyl units, sulfoisoterephthaloyl units, oxyethyleneoxy and oxy-1,2-propylene units. The repeat units form the backbone of the oligomer and are preferably terminated with modified isethionate end-caps. A particularly preferred soil release agent of this type comprises about one sulfoisophthaloyl unit, 5 terephthaloyl units, oxyethyleneoxy and oxy-1,2-propyleneoxy units in a ratio of from about 1.7 to about 1.8, and two end-cap units of sodium 2-(2-hydroxyethoxy)-ethanesulfonate. These sulfo-end-capped soil release agents also comprise from about 0.5% to about 20%, by weight of the oligomer, of a crystalline-reducing stabilizer, preferably selected from the group consisting of xylene sulfonate, cumene sulfonate, toluene sulfonate, and mixtures thereof.

If utilized, soil release agents will typically comprise from about 0.01% to about

Enzymes

Enzymes can be included in the formulations herein for a wide variety of fabric laundering or other cleaning purposes, including removal of protein-based, carbohydrate-based, or triglyceride-based stains, for example, and for the prevention of refugee dye transfer, and for fabric restoration. The enzymes to be incorporated include proteases, amylases, lipases, cellulases, and peroxidases, as well as mixtures thereof. Other types of enzymes may also be included. They may be of any suitable origin, such as vegetable, animal, bacterial, fungal and yeast origin. However, their choice is governed by several factors such as pH-activity and/or stability optima, thermostability, stability versus active detergents, builders, etc.. In this respect bacterial or fungal enzymes are preferred, such as bacterial amylases and proteases, and fungal cellulases.

Enzymes are normally incorporated at levels sufficient to provide up to about 5 mg by weight, more typically about 0.01 mg to about 3 mg, of active enzyme per gram of the composition. Stated otherwise, the compositions herein will typically comprise from about 0.001% to about 5%, preferably 0.01%-1% by weight of a commercial enzyme preparation. Protease enzymes are usually present in such commercial preparations at levels sufficient to provide from 0.005 to 0.1 Anson units (AU) of activity per gram of composition.

Suitable examples of proteases are the subtilisins which are obtained from particular strains of *B. subtilis* and *B. licheniformis*. Another suitable protease is obtained from a strain of *Bacillus*, having maximum activity throughout the pH range of 8-12, developed and sold by Novo Industries A/S as ESPERASE®. Proteolytic enzymes suitable for removing protein-based stains that are commercially available include those sold under the tradenames ALCALASE® and SAVINASE® by Novo Industries A/S (Denmark) and MAXATASE® by International Bio-Synthetics, Inc. (The Netherlands). Other proteases include Protease A (see European Patent Application 130,756, published January 9, 1985), Protease B (see European Patent Application Serial No. 87303761.8, filed April 28, 1987, and European Patent Application 130,756, Bott et al, published January 9, 1985) and "Protease D" as described in the patent applications of A. Baeck, et al, entitled "Protease-Containing Cleaning Compositions" having U.S. Serial No. 08/322,676, and C. Ghosh, et al, "Bleaching Compositions Comprising Protease Enzymes" having U.S. Serial No. 08/322,677, both filed October 13, 1994, and also in WO 95/10615, published April 20, 1995.

and TERMAFLEX® by Novo Industries. Also suitable are amylases having the commonality of being derived using site-directed mutagenesis from one or more of the

Bacillus amylases, especially the *Bacillus* alpha-amylases, regardless of whether one, two or multiple amylase strains are the immediate precursors.

"Oxidative stability-enhanced" amylases may also be employed and are non-limitingly illustrated by the following:

(a) An amylase according to the hereinbefore incorporated WO/94/02597, Novo Nordisk A/S, published Feb. 3, 1994, as further illustrated by a mutant in which substitution is made, using alanine or threonine (preferably threonine), of the methionine residue located in position 197 of the *B.licheniformis* alpha-amylase, known as TERMAMYL®, or the homologous position variation of a similar parent amylase, such as *B. amyloliquefaciens*, *B. subtilis*, or *B. stearothermophilus*;

(b) Stability-enhanced amylases as described by Genencor International in a paper entitled "Oxidatively Resistant alpha-Amylases" presented at the 207th American Chemical Society National Meeting, March 13-17 1994, by C. Mitchinson. Therein it was noted that bleaches detergents inactivate alpha-amylases but that improved oxidative stability amylases have been made by Genencor from *B.licheniformis* NCIB8061. Methionine (Met) was identified as the most likely residue to be modified. Met was substituted, one at a time, in positions 8,15,197,256,304,366 and 438 leading to specific mutants, particularly important being M197L and M197T with the M197T variant being the most stable expressed variant;

(c) Particularly preferred herein are amylase variants having additional modification in the immediate parent available from Novo Nordisk A/S. These amylases include those commercially marketed as DURAMYL by NOVO; bleach-stable amylases are also commercially available from Genencor.

Any other oxidative stability-enhanced amylase can be used, for example as derived by site-directed mutagenesis from known chimeric, hybrid or simple mutant parent forms of available amylases.

Cellulases usable in, but not preferred, for the present invention include both bacterial or fungal cellulases. Typically, they will have a pH optimum of between 5 and 9.5. Suitable cellulases are disclosed in U.S. Patent 4,435,307, Barbesgoard et al, issued March 6, 1984, which discloses fungal cellulase produced from *Humicola insolens* and *Humicola* strain DSM1800 or a cellulase 212-producing fungus belonging to the genus *Aeromones* and cellulase extracted from the filamentous fungus *Trichoderma reesei*.

especially useful.

Suitable lipase enzymes for detergent use include those produced by microorganisms of the *Pseudomonas* group, such as *Pseudomonas stutzeri* ATCC 19.154, as disclosed in British Patent 1,372,034. See also lipases in Japanese Patent Application 53,20487, laid open to public inspection on February 24, 1978. This lipase is available from Amano Pharmaceutical Co. Ltd., Nagoya, Japan, under the trade name Lipase P "Amano," hereinafter referred to as "Amano-P." Other commercial lipases include Amano-CES, lipases ex *Chromobacter viscosum*, e.g. *Chromobacter viscosum* var. *lipolyticum* NRRLB 3673, commercially available from Toyo Jozo Co., Tagata, Japan; and further *Chromobacter viscosum* lipases from U.S. Biochemical Corp., U.S.A. and Disoynth Co., The Netherlands, and lipases ex *Pseudomonas gladioli*. The LIPOLASE® enzyme derived from *Humicola lanuginosa* and commercially available from Novo (see also EPO 341,947) is a preferred lipase for use herein. Another preferred lipase enzyme is the D96L variant of the native *Humicola lanuginosa* lipase, as described in WO 92/05249 and Research Disclosure No. 35944, March 10, 1994, both published by Novo.

Peroxidase enzymes can be used in combination with oxygen sources, e.g., percarbonate, perborate, persulfate, hydrogen peroxide, etc. They are typically used for "solution bleaching," i.e. to prevent transfer of dyes or pigments removed from substrates during wash operations to other substrates in the wash solution. Peroxidase enzymes are known in the art, and include, for example, horseradish peroxidase, ligninase, and haloperoxidase such as chloro- and bromo-peroxidase. Peroxidase-containing detergent compositions are disclosed, for example, in PCT International Application WO 89/099813, published October 19, 1989, by O. Kirk, assigned to Novo Industries A/S. The present invention encompasses peroxidase-free automatic dishwashing composition embodiments.

Other Ingredients

Usual detergent ingredients can include one or more materials for assisting or enhancing cleaning performance, treatment of the substrate to be cleaned, or to modify the aesthetics of the composition. Usual deterative adjuncts of detergent compositions include the ingredients set forth in U.S. Pat. No. 3,936,537, Baskerville et al. Adjuncts which can also be included in the compositions employed in the present invention, in

addition to the above, may include, for example, anti-tarnish agents and corrosion inhibitors, agents, dyes, fillers, optical brighteners, germicides, alkalinity sources, hydrotropes, anti-

oxidants, enzyme stabilizing agents, perfumes, dyes, solubilizing agents, clay soil remolval/anti-redeposition agents, carriers, processing aids, pigments, solvents for liquid formulations, fabric softeners, static control agents, solid fillers for bar compositions, etc. Dye transfer inhibiting agents, including polyamine N-oxides such as polyvinylpyridine N-oxide can be used. Dye-transfer-inhibiting agents are further illustrated by polyvinylpyrrolidone and copolymers of N-vinyl imidazole and N-vinyl pyrrolidone. If high sudsing is desired, suds boosters such as the C₁₀-C₁₆ alkanolamides can be incorporated into the compositions, typically at 1%-10% levels. The C₁₀-C₁₄ monoethanol and diethanol amides illustrate a typical class of such suds boosters. Use of such suds boosters with high sudsing adjunct surfactants such as the amine oxides, betaines and sultaines noted above is also advantageous. If desired, soluble magnesium salts such as MgCl₂, MgSO₄, and the like, can be added at levels of, typically, 0.1%-2%, to provide additional suds and to enhance grease removal performance.

Liquid Compositions

The present invention comprises both liquid and granular compositions including the aforementioned ingredients. Liquid compositions, including gels, typically contain some water and other fluids as carriers. Low molecular weight primary or secondary alcohols exemplified by methanol, ethanol, propanol, and isopropanol are suitable. Monohydric alcohols are preferred for solubilizing surfactant, but polyols such as those containing from 2 to about 6 carbon atoms and from 2 to about 6 hydroxy groups (e.g., 1,3-propanediol, ethylene glycol, glycerine, and 1,2-propanediol) can also be used. The compositions may contain from 5% to 90%, typically 10% to 50% of such carriers. Liquid compositions according to the present invention may be formulated acidic to deliver an in-use alkaline pH. Low pH formulation is generally from about 2 to about 5 and preferably from about 2.5 to about 4.5. In-use pH is may range from about 7 to about 11, preferably from about 9.5 to about 10.5.

Emulsifying system and/or a thickening system may also be required. The emulsifying or thickening system provide suitable storage length and stability profiles. The emulsifying system is typically composed of a nonionic surfactant, mixtures of nonionic surfactants or mixtures of anionic and nonionic surfactants.

The following examples are provided to illustrate the invention.

Example 1: Aqueous Composition

Those skilled in the art will realize that, in the simplest case, a rheology capable of suspending solids is simply a viscosity sufficient to prevent settling, creaming,

floccing, etc., of the particles being suspended. The required viscosity will vary according to particle size but should generally be greater than about 300 cps (measured at 10 rpm). It will further be realized by those skilled in the art the rheology will preferably be that of a non-Newtonian, shear thinning fluid. Such fluids exhibit very high viscosities at low shear with viscosity reducing as shear is increased e.g. a shear thinning fluid may have a viscosity of 2000 cps at 10 rpm but only 500 cps at 100 rpm. Such shear thinning systems may be obtained in several ways including the use of associative polymeric thickeners, emulsions and specific surfactant systems.

Coating

Various deterative ingredients employed in the present compositions optionally can be further stabilized by absorbing the ingredients onto a porous hydrophobic substrate, then coating the substrate with a hydrophobic coating. Preferably, the deterative ingredient is admixed with a surfactant before being absorbed into the porous substrate. In use, the deterative ingredient is released from the substrate into the aqueous washing liquor, where it performs its intended deterative function.

To illustrate this technique in more detail, a porous hydrophobic silica (trademark SIPERNAT®D10, Degussa) is admixed with a proteolytic enzyme solution containing 3%-5% of C₁₃₋₁₅ ethoxylated alcohol (EO 7) nonionic surfactant. Typically, the enzyme/surfactant solution is 2.5X the weight of silica. The resulting powder is dispersed with stirring in silicone oil (various silicone oil viscosities in the range of 500-12,500 can be used). The resulting silicone oil dispersion is emulsified or otherwise added to the final detergent matrix. By this means, ingredients such as the aforementioned enzymes, hydrogen peroxide sources, bleach activators, bleach catalysts, photoactivators, dyes, fluorescers, fabric conditioners and hydrolyzable surfactants can be "protected" for use in detergents, including liquid laundry detergent compositions. Alternate forms of coating particles, such as for example wax encapsulation, are disclosed in U.S. Patent Nos. 4,087,369, 5,230,822 and 5,200,236.

Bar Compositions

The compositions of the present invention may also be employed in laundry or cleaning bar forms. Bar forms typically include a surfactant (including soap), a color

care agent, and the such bar composition according to the present invention comprises in addition to the color care agent from about 10% to about 90% surfactant (including soap

or mixtures thereof with conventional synthetic surfactants, from about 0.1% to about 40% sodium perborate as peroxide source, from about 0.1% to about 20% activator, from about 0.1% to about 50% builder, and optionally from about 0.1% to about 60% of organic or inorganic fillers such as talc, starch or the like. Suitable bar compositions and the methods of manufacture are disclosed in U.S. Patent Nos. 4,151,105, 3,248,333, 5,340,492 and 5,496,488, the disclosures of which are herein incorporated by reference, and in Great Britain Application 2,096,163A.

Granular Compositions

The bleaching and bleach additive compositions of the present invention can be used in both low density (below 550 grams/liter) and high density granular compositions in which the density of the granule is at least 550 grams/liter. Granular compositions are typically designed to provide an in the wash pH of from about 7.5 to about 11.5, more preferably from about 9.5 to about 10.5. Low density compositions can be prepared by standard spray-drying processes. Various means and equipment are available to prepare high density compositions. Current commercial practice in the field employs spray-drying towers to manufacture compositions which have a density less than about 500 g/l. Accordingly, if spray-drying is used as part of the overall process, the resulting spray-dried particles must be further densified using the means and equipment described hereinafter. In the alternative, the formulator can eliminate spray-drying by using mixing, densifying and granulating equipment that is commercially available. The following is a nonlimiting description of such equipment suitable for use herein.

Various means and equipment are available to prepare high density (i.e., greater than about 550, preferably greater than about 650, grams/liter or "g/l"), high solubility, free-flowing, granular detergent compositions according to the present invention. Current commercial practice in the field employs spray-drying towers to manufacture granular laundry detergents which often have a density less than about 500 g/l. In this procedure, an aqueous slurry of various heat-stable ingredients in the final detergent composition are formed into homogeneous granules by passage through a spray-drying tower, using conventional techniques, at temperatures of about 175°C to about 225°C. However, if spray drying is used as part of the overall process herein, additional process steps as described hereinafter must be used to obtain the final product of the present invention.

Liquid such as water or a nonionic surfactant into the pores of the granules and/or subjecting them to one or more high speed mixer-densifiers. A suitable high speed

mixer/densifier for this process is a device marketed under the tradename "Lödige CB 30" or "Lödige CB 30 Recycler" which comprises a static cylindrical mixing drum having a central rotating shaft with mixing/cutting blades mounted thereon. In use, the ingredients for the detergent composition are introduced into the drum and the shaft/blade assembly is rotated at speeds in the range of 100-2500 rpm to provide thorough mixing/densification. See Jacobs et al, U.S. Patent 5,149,455, issued September 22, 1992. The preferred residence time in the high speed mixer/densifier is from about 1 to 60 seconds. Other such apparatus includes the devices marketed under the tradename "Shugi Granulator" and under the tradename "Drais K-TTP 80).

Another process step which can be used to densify further spray-dried granules involves grinding and agglomerating or deforming the spray-dried granules in a moderate speed mixer/densifier so as to obtain particles having lower intraparticle porosity. Equipment such as that marketed under the tradename "Lödige KM" (Series 300 or 600) or "Lödige Ploughshare" mixer/densifiers are suitable for this process step. Such equipment is typically operated at 40-160 rpm. The residence time of the detergent ingredients in the moderate speed mixer/densifier is from about 0.1 to 12 minutes. Other useful equipment includes the device which is available under the tradename "Drais K-T 160". This process step which employs a moderate speed mixer/densifier (e.g. Lödige KM) can be used by itself or sequentially with the aforementioned high speed mixer/densifier (e.g. Lödige CB) to achieve the desired density. Other types of granules manufacturing apparatus useful herein include the apparatus disclosed in U.S. Patent 2,306,898, to G. L. Heller, December 29, 1942.

While it may be more suitable to use the high speed mixer/densifier followed by the low speed mixer/densifier, the reverse sequential mixer/densifier configuration is also contemplated by the invention. One or a combination of various parameters including residence times in the mixer/densifiers, operating temperatures of the equipment, temperature and/or composition of the granules, the use of adjunct ingredients such as liquid binders and flow aids, can be used to optimize densification of the spray-dried granules in the process of the invention. By way of example, see the processes in Appel et al, U.S. Patent 5,133,924, issued July 28, 1992 (granules are brought into a deformable state prior to densification); Delwel et al, U.S. Patent 4,637,891, issued January 20, 1987 (granulating spray-dried granules with a liquid binder and aluminosilicate); Kruse et al

U.S. Pat. 5,133,924, issued July 28, 1992, incorporated by reference.

In those situations in which particularly heat sensitive or highly volatile detergent ingredients are to be incorporated into the final detergent composition, processes which do not include spray drying towers are preferred. The formulator can eliminate the spray-drying step by feeding, in either a continuous or batch mode, starting detergent ingredients directly into mixing/densifying equipment that is commercially available. One particularly preferred embodiment involves charging a surfactant paste and an anhydrous builder material into a high speed mixer/densifier (e.g. Lödige CB) followed by a moderate speed mixer/densifier (e.g. Lödige KM) to form high density detergent agglomerates. See Capeci et al, U.S. Patent 5,366,652, issued November 22, 1994 and Capeci et al, U.S. Patent 5,486,303, issued January 23, 1996. Optionally, the liquid/solids ratio of the starting detergent ingredients in such a process can be selected to obtain high density agglomerates that are more free flowing and crisp.

Optionally, the process may include one or more recycle streams of undersized particles produced by the process which are fed back to the mixer/densifiers for further agglomeration or build-up. The oversized particles produced by this process can be sent to grinding apparatus and then fed back to the mixing/densifying equipment. These additional recycle process steps facilitate build-up agglomeration of the starting detergent ingredients resulting in a finished composition having a uniform distribution of the desired particle size (400-700 microns) and density (> 550 g/l). See Capeci et al, U.S. Patent 5,516,448, issued May 14, 1996 and Capeci et al, U.S. Patent 5,489,392, issued February 6, 1996. Other suitable processes which do not call for the use of spray-drying towers are described by Bollier et al, U.S. Patent 4,828,721, issued May 9, 1989; Beerse et al, U.S. Patent 5,108,646, issued April 28, 1992; and, Jolicœur, U.S. Patent 5,178,798, issued January 12, 1993.

In yet another embodiment, the high density detergent composition of the invention can be produced using a fluidized bed mixer. In this process, the various ingredients of the finished composition are combined in an aqueous slurry (typically 80% solids content) and sprayed into a fluidized bed to provide the finished detergent granules. Prior to the fluidized bed, this process can optionally include the step of mixing the slurry using the aforementioned Lödige CB mixer/densifier or a "Flexomix 160" mixer/densifier, available from Shugi. Fluidized bed or moving beds of the type available under the trade name "Fischer-Wild" can be used in such a process.

and optionally other detergent ingredients into a high speed mixer densifier (residence time 5-30 seconds) so as to form agglomerates containing a partially or totally

neutralized anionic surfactant salt and the other starting detergent ingredients. Optionally, the contents in the high speed mixer/densifier can be sent to a moderate speed mixer/densifier (e.g. Lödige KM) for further agglomeration resulting in the finished high density detergent composition. See Appel et al, U.S. Patent 5,164,108, issued November 17, 1992.

Optionally, high density detergent compositions according to the invention can be produced by blending conventional or densified spray-dried detergent granules with detergent agglomerates in various proportions (e.g. a 60:40 weight ratio of granules to agglomerates) produced by one or a combination of the processes discussed herein. Additional adjunct ingredients such as enzymes, perfumes, brighteners and the like can be sprayed or admixed with the agglomerates, granules or mixtures thereof produced by the processes discussed herein. Compositions in granular form typically limit water content, for example, to less than about 7% free water, for best storage stability.

The present invention will now be described by reference to the following examples. Of course, one of ordinary skill in the art will recognize that the present invention is not limited to the specific examples herein described or the ingredients and steps contained therein, but rather, may be practiced according to the broader aspects of the disclosure.

EXAMPLE I

Compositions having the form of granular laundry detergents are exemplified by the following formulations.

	A	B	C	D	E
INGREDIENT	%	%	%	%	%
NOBS	5	3.5	1	3.5	2
Sodium Percarbonate	0	0	19	21	0
Sodium Perborate monohydrate	21	0	0	0	20
Sodium Perborate tetrahydrate	12	21	0	0	0
Tetraacetylenediamine	0	0	0	1	0
Nonanoyloxybenzenesulfonate	0	0	3	0	0
Linear alkylbenzenesulfonate	5.5	11	19	12	9.5
Alkyl ethoxylate (C45E7)					

Trisodium citrate	5	5	2	3	3
-------------------	---	---	---	---	---

Acrylic Acid/Maleic Acid copolymer	4	0	4	5	0
Sodium polyacrylate	0	3	0	0	3
Diethylenetriamine penta(methylene phosphonic acid)	0.4	0	0.4	0	0
Color Care Agent ¹	3	2	4	3	2.5
Carboxymethylcellulose	0.3	0	0	0.4	0
Protease	1.4	0.3	1.5	2.4	0.3
Lipolase	0.4	0	0	0.2	0
Carezyme	0.1	0	0	0.2	0
Anionic soil release polymer	0.3	0	0	0.4	0.5
Dye transfer inhibiting polymer	0	0	0.3	0.2	0
Carbonate	16	14	24	6	23
Silicate	3.0	0.6	12.5	0	0.6
Sulfate, Water, Perfume, Colorants	to 100	to 100	to 100	to 100	to 100

1) N,N,N',N'-tetrakis-(2-hydroxypropyl)ethylenediamine

EXAMPLE II

A laundry bar suitable for hand-washing soiled fabrics is prepared by standard extrusion processes and comprises the following:

<u>Component</u>	<u>Weight %</u>
Color Care Agent ¹	3
NOBS	4
Sodium Perborate Tetrahydrate	12
C ₁₂ linear alkyl benzene sulfonate	30
Phosphate (as sodium tripolyphosphate)	10
Sodium carbonate	5
Sodium pyrophosphate	7
Coconut monoethanolamide	2
Zeolite A (0.1-10 micron)	5
Carboxymethylcellulose	0.2
Soil release	1
CaSO ₄	1
MgSO ₄	1

Water

4

Filler**

Balance to 100%

1) N,N,N',N'-tetrakis-(2-hydroxypropyl)ethylenediamine

**Can be selected from convenient materials such as CaCO₃, talc, clay, silicates, and the like. Acidic fillers can be used to reduce pH.

Fabrics are washed with the bar with excellent results.

EXAMPLE III

The following liquid detergent compositions are made :


Ingredient	Example a	Example b	Example c
	Wt %	Wt %	Wt%
C12-15alkyl polyethoxylate (1.8) sulfate	21.4	20.2	--
C12-15alkyl polyethoxylate (2.5) sulfate	-	-	19.0
Ethanol	3.7	3.6	3.4
Monoethanolamine	1.0	1.0	1.0
C10 amidopropyldimethyl amine	0.5	0.5	--
Propandiol	6.8	6.4	6.2
C12-13Alkyl polyethoxylate (9)	0.7	0.6	2.0
C12-14 alkyl glucose amide	2.7	2.5	3.5
C12-14 fatty acid	2.0	2.0	2.0
Sodium oluene sulfonate	2.3	2.5	2.5
Citric acid	3.5	3.0	3.0
Borax	2.5	2.5	2.5
Sodium hydroxide (to pH 8.0)	2.5	2.5	3.0
Lipolase (100KLU/g)	0.1	0.08	0.04
Amylase (300KNU/g)	0.2	0.2	0.1
Carezyme (5000cevu/g)	0.05	0.5	0.3
Protease (32g/L)	0.9	0.8	1.0
Soil Release Polymer*	0.2	0.5	0.3
Color Care Agent ¹	2.0	3.0	2.5
Water, perfume, enzymes, suds suppressor, brightener & other optional ingredients	to 100%	to 100%	to 100%

* Oligomer of Sodium 2-[2-(2-Hydroxyethoxy)ethoxy]ethanesulfonate, Dimethyl Terephthalate, Sodium 2-(2,3-Dihydroxypropoxy)ethanesulfonate, Ethylene Glycol and Propylene Glycol.

What is claimed is:

1. A detergent composition comprising:

- (A) from about 0.1% to about 50% of by weight of the composition of a
5 color care agent having the formula:




- wherein X is selected from the group consisting of hydrogen; linear or branched,
10 substituted or unsubstituted alkyl having from 1-10 carbons atoms and substituted or
unsubstituted aryl having at least 6 carbon atoms; n is an integer from 1 to 6; R₁, R₂,
R₃, and R₄ are independently selected from the group consisting of alkyl; aryl; alkaryl;
arylalk; hydroxyalkyl; polyhydroxyalkyl; polyalkylether having the formula -
((CH₂)_yO)_zR₇ where R₇ is hydrogen or a linear, branched, substituted or unsubstituted
15 alkyl chain having from 1 to 10 carbon atoms and where y is an integer from 2 to 10
and z is an integer from 1 to 30; alkoxy; polyalkoxy having the formula: -
(O(CH₂)_y)_zR₈; the group -C(O)R₈ where R₈ is alkyl; alkaryl; arylalk; hydroxyalkyl;
polyhydroxyalkyl and polyalkylether as defined in R₁, R₂, R₃, and R₄;
CX₂CX₂N(R₅)(R₆) with no more than one of R₁, R₂, R₃, and R₄ being
20 CX₂CX₂N(R₅)(R₆) and wherein R₅ and R₆ are alkyl; alkaryl; arylalk; hydroxyalkyl;
polyhydroxyalkyl, polyalkylether, alkoxy and polyalkoxy as defined in R₁, R₂, R₃, and
R₄; and either of R₁ + R₃ or R₄ or R₂ + R₃ or R₄ can combine to form a cyclic
substituent; and

- B) from about 5% to about 99.9%, by weight, of detergent adjunct
25 ingredients selected from the group consisting of surfactants, builders, bleaching
agents, enzymes, soil release polymers, dye transfer inhibitors, and mixtures thereof.

2. The detergent composition as claimed in Claim 1 wherein any of R₁, R₂, R₃, and
R₄ are independently selected from the group consisting of hydrogen, alkyl groups
30 having from 1 to 5 carbon atoms and hydroxyalkyl groups having from 1 to 5 carbon
atoms.

4. The detergent composition as claimed in any of Claims 1-3 wherein each of R₁, R₂, R₃, and R₄ are hydroxyalkyl groups having from 1 to 5 carbon atoms.
- 40 5. The detergent composition as claimed in any of Claims 1-4 wherein said color care agent has more than about 1% nitrogen by weight of the compound.
6. The detergent composition as claimed in any of Claims 1-5 wherein said color care agent has more than about 7% nitrogen by weight of the compound.
- 45 7. The detergent composition as claimed in any of Claims 1-6 further comprising from about 5% to about 80%, by weight, of a detergent builder and from about 5% to about 80%, by weight, of deterative surfactant.
- 50 8. The detergent composition as claimed in any of Claims 1-7 wherein said composition is in granular form having a bulk density of at least about 550 g/L.
9. The detergent composition as claimed in any of Claims 1-7 wherein said composition is in liquid form and further comprises from about 5% to about 90% by weight of the composition of a liquid carrier.
- 55 10. A granular detergent composition comprising:
 (A) from about 0.1% to about 50% of by weight of the composition of a color care agent having the formula:

60



- wherein X is selected from the group consisting of hydrogen; linear or branched, substituted or unsubstituted alkyl having from 1-10 carbons atoms and substituted or unsubstituted aryl having at least 6 carbon atoms; n is an integer from 1 to 6; R₁, R₂, R₃, and R₄ are independently selected from the group consisting of alkyl; aryl; alkaryl; arylalk; hydroxyalkyl; polyhydroxyalkyl; polyalkylether having the formula - ((CH₂)_yO)_zR₇ where R₇ is hydrogen or a linear, branched, substituted or unsubstituted
- 65

polyhydroxyalkyl and polyalkylether as defined in R₁, R₂, R₃, and R₄:

CX₂CX₂N(R₅)(R₆) with no more than one of R₁, R₂, R₃, and R₄ being
CX₂CX₂N(R₅)(R₆) and wherein R₅ and R₆ are alkyl; alkaryl; arylalk; hydroxyalkyl;
75 polyhydroxyalkyl, polyalkylether, alkoxy and polyalkoxy as defined in R₁, R₂, R₃, and
R₄; and either of R₁ + R₃ or R₄ or R₂ + R₃ or R₄ can combine to form a cyclic
substituent; and

B) from about 5% to about 99.9%, by weight, of detergent adjunct
ingredients selected from the group consisting of surfactants, builders, bleaching
80 agents, enzymes, soil release polymers, dye transfer inhibitors, and mixtures thereof;
wherein said granular composition has a bulk density of at least about 550 g/L.

INTERNATIONAL SEARCH REPORT

Int'l Application No
PCT/US 98/02255

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 C1103/30 C11017/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C110

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
X	US 4 263 179 A (SCHMOLKA IRVING R) 21 April 1981 see claims 1-8	1-7,9
X	EP 0 206 513 A (PROCTER & GAMBLE ; PROCTER & GAMBLE EUROP (BE)) 30 December 1986 see claims	1-7,9
X	WO 97 00929 A (PROCTER & GAMBLE ; MORELLI JOSEPH PAUL (US); LAPPAS DIMITRIS (BE);) 9 January 1997 see claim 1; examples	1
X	FR 2 617 183 A (CAMP SA) 30 December 1988 see claims	1,8,10
	-/--	

☒ Further documents are listed in the continuation of box C

☒ Patent family members are listed in annex

* Special categories of cited documents

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is taken in combination with other prior art

09/06/1998

09/06/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2
NL-2280 HV Rijswijk
Tel. +31 (0) 74 454 1111
Fax +31 (0) 74 454 1111

Authorized officer

INTERNATIONAL SEARCH REPORT

Int. tional Application No

PCT/US 98/02255

C (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication where appropriate, of the relevant passages	Relevant to claim No
A	DE 22 26 871 A (HENKEL & CIE GMBH) 20 December 1973 see claims -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. tional Application No

PCT/US 98/02255

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4263179	A	21-04-1981	CA 1134709 A	02-11-1982
			US 4321167 A	23-03-1982
EP 0206513	A	30-12-1986	CA 1309925 A	10-11-1992
WO 9700929	A	09-01-1997	WO 9612000 A	25-04-1996
			AU 1288195 A	06-05-1996
			AU 3686995 A	06-05-1996
			CA 2202505 A	25-04-1996
			CZ 9701109 A	17-09-1997
			CZ 9701110 A	17-09-1997
			EP 0785978 A	30-07-1997
			EP 0833884 A	08-04-1998
			EP 0785981 A	30-07-1997
			WO 9612004 A	25-04-1996
FR 2617183	A	30-12-1988	FR 2552446 A	29-03-1985
			EP 0139547 A	02-05-1985
DE 2226871	A	20-12-1973	NONE	